




TYPE A




TOP VIEW




**TYPE D
FOR GROUND MOUNTED
CONTROLLER CABINET**



**TOP VIEW
TYPICAL ONE BUTTON INSTALLATION**



**TOP VIEW
TYPICAL TWO BUTTON INSTALLATION**




**PEDESTRIAN PUSH BUTTON
POST INSTALLATION**

All dimensions are in millimeters (inches)
unless otherwise shown.

DATE	REVISIONS
1-1-04	Revised Type E foundation table.
1-1-03	Added alternate Type E foundation depths and diameters.

**CONCRETE
FOUNDATION DETAILS**
(Sheet 1 of 2)

STANDARD 878001-02



Mast Arm Length	① Foundation Depth *	② Foundation Diameter	③ Spiral Diameter	④ Quantity of No. 15 (No. 5) Bars
Less than 9.1 m (30')	3.0 m (10'-0")	750 (30)	600 (24)	8
Greater than or equal to 9.1 m (30') and less than 12.2 m (40')	4.1 m (13'-6")	750 (30)	600 (24)	8
Greater than or equal to 12.2 m (40') and less than 15.2 m (50')	3.4 m (11'-0")	900 (36)	750 (30)	12
Greater than or equal to 15.2 m (50') and up to 16.8 m (55')	4.0 m (13'-0")	900 (36)	750 (30)	12
Greater than or equal to 16.8 m (55')	4.6 m (15'-0")	900 (36)	750 (30)	12

* These foundation depths are for sites which have cohesive soils (clayey silt, sandy clay, etc.) along the length of the shaft, with an average Unconfined Compressive Strength (Q_u) > 100 kPa (1.0 tsf). This strength shall be verified by boring data prior to construction or with testing by the Engineer during foundation drilling. The Bureau of Bridges & Structures should be contacted for a revised design if other conditions are encountered.

TYPE E

All dimensions are in millimeters (inches) unless otherwise shown.